

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-039.2-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineralwool (MW) products (details cf. annex)

placed on the market by

**DEUTSCHE ROCKWOOL
GmbH & Co. KG**
Rockwool Straße 37-41
45966 Gladbeck
Germany

and produced in the factory

ROCKWOOL, a.s.
Cihelní 769
735 31 Bohumín 3
Czech Republik

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 are applied and that

the essential characteristics of reaction to fire for the products fulfil all the prescribed requirements set out above

This certificate was first issued on 29.01.2014 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard (but no longer than 18.11.2018), used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly

Gräfelfing, 19.11.2017



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht

A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München.



Factory: ROCKWOOL, a.s., Cihelní 769, 735 31 Bohumín 3, Czech Republik

Construction product(s): Factory made mineralwool (MW) products according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire: for uses subject to regulations on reaction to fire A2L. Products for which a clearly identifiable stage in the production process results in an improvement of the classification by limiting of organic material.

Attestation of conformity system: 1

No.	Product			Reaction to fire EN 13501-1				
	Form	Type	Description	Classification	Range	max. organic content	Report. No	Classification report
1	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section covered with a rein-forced aluminium foil Production line: BOH 2/CIRK 3	A2L-s1, d0	Density: 90 - 110 kg/m ³ Wall thickness: 20 mm to 60 mm	4,0 mass% and 4,4 kg/m ³	6	230009473-3

Detail information about the insulation products are given in the classification reports
 Gräfelfing 19.11.2017



Head of Certification Body

Dipl.-Ing. (FH) Wolfgang Albrecht