

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-039.0-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineralwool (MW) products (details cf. annex)

placed on the market by **ROCKWOOL Polska Sp. z o. o.**
Ul. Kwiatowa 14
33-131 Cigacice
Poland

and produced in the factory **ROCKWOOL, a.s.**
Cihelní 769, Skřečůň
735 31 Bohumín
Czech Republik

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 are applied and that

the essential characteristics of reaction to fire for the products fulfil all the prescribed requirements set out above

This certificate was first issued on 04.07.2014 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard (but no longer than 08.01.2019), used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly

Gräfelfing, 08.01.2018



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht

A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München.

Forschungsinstitut für Wärmeschutz e. V. München
 Annex to Certificate of Constancy of Performance: 0751-CPR-2-039-0-01
 Date: 08.01.2018

Factory: ROCKWOOL, a.s., Cihelni 769, Skřečůň, 735 31 Bohumin, Czech Republik
 Construction product(s): Factory made mineralwool (MW) products according to EN 14303:2009+A1:2013
 Intended use: Thermal insulation products for building equipment and industrial installations
 Level(s) or class(es) reaction to fire: for uses subject to regulations on reaction to fire A2 and A2L. Products for which a clearly identifiable stage in the production process results in an improvement of the classification by limiting of organic material.

Attestation of conformity system: 1

No.	Product			Reaction to fire EN 13501-1				
	Form	Type	Description	Classification	Range	max. organic content	Report. No	Classification report
1	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section covered with a rein-forced aluminium foil Production line: BOH2 & PSM 1,2	A2L-s1,d0	Density: 90 - 150 kg/m ³ Wall thickness: ≥ 20 mm	3,0 mass% and 4,2 kg/m ³	1	230010154-4
2	Pipe section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section covered with a rein-forced aluminium foil Production line: BOH2 & PSM 1,2	A2-s1,d0	Density: 90 - 140 kg/m ³ Wall thickness: 20 mm to 120 mm Outer diameter > 300mm	3,0 mass% and 4,2 kg/m ³	5	230010154-4
3	Pipe section	Teclit PS	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil Production line: BOH2 & CIRK 3	A2L-s1,d0	Density: 90 kg/m ³ to 110 kg/m ³ Thickness: 20 mm to 60 mm	3,8 mass% and 4,4 kg/m ³	6	230011021-3

Detail information about the insulation products are given in the classification reports
 Graßelfing 08.01.2018



Head of Certification Body

W. Albrecht

Dipl.-Ing. (FH) Wolfgang Albrecht