

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-008.3-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineralwool (MW) products (details cf. annex)

placed on the market by **Rockwool Polska SP z o.o.**
Kwiatowa 14
66-131 Cigacice
Poland

and produced in the factory **Rockwool B.V.**
Industrieweg 15
6040 KD Roermond
Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 are applied and that

the essential characteristics of reaction to fire for the products fulfil all the prescribed requirements set out above

This certificate was first issued on 09.09.2016 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard (but no longer than 02.07.2019), used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Gräfelfing, 03.07.2018



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht

A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München.

Factory: Rockwool B.V., Industrieweg 15, 6040 KD Roermond, Netherlands

Construction product(s): Factory made mineralwool (MW) products according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire: for uses subject to regulations on reaction to fire A2 and A2L. Products for which a clearly identifiable stage in the production process results in an improvement of the classification by limiting of organic material.

Attestation of conformity system: 1

No.	Product		Reaction to fire EN 13501-1				
	Form	Type	Description	Classification	Range	Report. No	Classification report
1	Pipe Section	Teclit PS	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil	A2L-s1,d0	Do ≤ 300 mm Max. organic content: 3,1 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm	4	230010470-3
2	Pipe Section	Teclit PS	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil	A2-s1,d0	Do > 300 mm Max. organic content: 3,1 kg/m ³ Density: 100 kg/m ³ ± 15 % Thickness: ≥ 20 mm	6	230010471-2
3	Pipe Section	Rockwool 800	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil	A2L-s1,d0	Do ≤ 300 mm Max. organic content: 2,33 kg/m ³ Density: 90 kg/m ³ - 100 kg/m ³ Thickness: ≥ 20 mm Production line ROE 2, PU 2	3	230007518-3

Detail information about fire insulation products are given in the classification reports
 Gräfelfing 03.07.2018



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht